



MICKEY THOMPSON
M/T
TIRES & WHEELS

LIGHT TRUCK TIRE GUIDE



FORGE YOUR LEGACY.

LEGACIES AREN'T BUILT OVERNIGHT—THEY'RE FORGED IN THE DIRT, THROUGH RELENTLESS DRIVE, UNSHAKABLE DETERMINATION, AND THE WILL TO PUSH PAST EVERY OBSTACLE. EVERY TRAIL CONQUERED, EVERY CHALLENGE OVERCOME, AND EVERY BUILD PERFECTED BECOMES PART OF A LASTING STORY OF GRIT AND PERFORMANCE. THAT SPIRIT FUELS EVERY PRODUCT MICKEY THOMPSON CREATES, BUILT TO SUPPORT THOSE CHASING GREATNESS AND FORGING THEIR OWN LEGACY.

TABLE OF CONTENTS

LIGHT TRUCK TIRES

THE RIGHT TRUCK & SUV TIRE FOR EVERY LIFESTYLE	3
WHY MICKEY THOMPSON TIRES LEAD THE PACK	4
BAJA BOSS® A/T	10 / 22
BAJA LEGEND EXP™	11 / 24
BAJA BOSS® M/T	12 / 26
BAJA LEGEND MTZ™	13 / 28

EXTREME TERRAIN TIRES

ALL-NEW BAJA BELTED™ II	16 / 30
BAJA PRO® X	18 / 30
BAJA PRO® XS	19 / 32
BAJA BOSS® X	20 / 32
BAJA BOSS® XS	21 / 32
WARRANTY INFORMATION	34

LIGHT TRUCK TIRES

A VAST RANGE OF FITMENTS FOR ALL OF YOUR ON AND OFF-ROAD NEEDS. FROM WEEKEND WARRIORS TO FULLY DECKED OUT OFF-ROAD RIGS, OUR LIGHT TRUCK TIRES ARE PURPOSE BUILT FOR EVERY TERRAIN AND EVERY ADVENTURE. SEE YOU OUT THERE!



THE RIGHT TRUCK & SUV TIRE FOR EVERY LIFESTYLE

Whether it's competition-proven off-road traction, on-road comfort, or all-weather capability, the Mickey Thompson Baja Boss® and Baja Legend™ light truck tire lineups provide the perfect options for your needs.



	BAJA BOSS® A/T	BAJA LEGEND EXP™	BAJA BOSS® M/T	BAJA LEGEND MTZ™
	PREMIUM HYBRID A/T - R/T	HYBRID A/T - R/T	PREMIUM MUD TERRAIN	MUD TERRAIN
	Extreme off-road allure with a premium on-road experience in any weather or terrain.	Ample off-road traction and rugged-looks with a dependable on-road experience.	Competition-proven, ultimate off-road experience coupled with aggressive styling.	Authentic mud-terrain styling and off-road performance blended with a comfortable ride.
LOW NOISE*	9	9	7	6
TREAD LIFE*	8	8	6	6
RIDE COMFORT*	7	9	8	8
AGGRESSIVE LOOKS*	8	6	10	8
SNOW TRACTION*	9	5	7	7
MUD TRACTION*	6	5	8	10
ROCK TRACTION*	8	6	10	9

*ON A SCALE OF 1-10, 10 BEING THE MOST PREFERABLE PERFORMANCE.



WHY MICKEY THOMPSON TIRES LEAD THE PACK

TREAD DESIGN

While the distinctive asymmetric tread patterns are unique to Mickey Thompson's Baja Boss® family of tires, all Mickey Thompson Light Truck and Off-Road tires features Sidebiters®, tread elements that extend onto the sidewall for added traction and protection. Whether you're cruising through weekend trails, showcasing your rig at the next big event or chasing a podium finish, Sidebiters® are engineered to help keep you moving forward with confidence!

SIDEBITER® COMPARISON		BAJA PRO® X	BAJA PRO® XS	BAJA BELTED® II	BAJA BOSS® X	BAJA BOSS® XS	BAJA BOSS® M/T	BAJA BOSS® A/T	BAJA LEGEND MTZ™	BAJA LEGEND EXP™
STANDARD SIDEBITERS®										X
UP TO 75% DEEPER*									X	
150% DEEPER*					X	X	X	X†		
225% DEEPER*				X						
350% DEEPER*		X	X							

*COMPARED TO STANDARD SIDEBITERS®
†LT SIZES ONLY



WHY MICKEY THOMPSON TIRES LEAD THE PACK

COMPOUND

We engineer compounds for specific performance needs—from silica blends that improve wet braking and tread life to competition-grade formulas for rock crawling and desert racing. Each mix is tuned to deliver in its environment and outperform the competition.

LT COMPOUND CODES		BAJA PRO® X	BAJA PRO® XS	BAJA BELTED® II	BAJA BOSS® X	BAJA BOSS® XS	BAJA BOSS® M/T	BAJA BOSS® A/T	BAJA LEGEND MTZ™	BAJA LEGEND EXP™
S1	Next-gen silica reinforced compound engineered to provide excellent wet handling/braking, lasting treadlife and cold/wet weather traction for lighter duty applications.							X*		
T1	Next-gen silica reinforced compound engineered to provide excellent wet handling/braking, lasting treadlife and cold/wet weather traction for heavy-duty applications.							X†		
T4	Silica reinforced tread compound engineered to provide excellent wet handling/braking performance, cut & chip resistance and lasting treadlife.					X	X		X	X
X3	Competition compound for long-distance, high-speed, and rock crawling competition. Equally at-home on a low powered/low-speed rock crawler. NOT FOR HIGHWAY USE.				X					
T5	Extremely durable compound developed for on and off-road use.		X	X						
X1	Competition compound developed for aggressive short-distance rock bouncing or low-speed rock crawling. NOT FOR HIGHWAY USE.	X								

*SUV SIZES ONLY

†LT SIZES ONLY



WHY MICKEY THOMPSON TIRES LEAD THE PACK

CONSTRUCTION

Our proprietary PowerPly™ technologies reinforce radial tires with bias-ply strength, improving puncture resistance, steering response, and sidewall durability. It's a hybrid construction built for real-world abuse—on-road, off-road, or off-the-map.

LT TIRE CONSTRUCTION			BAJA PRO® X	BAJA PRO® XS	BAJA BELTED® II	BAJA BOSS® X	BAJA BOSS® XS	BAJA BOSS® M/T	BAJA BOSS® A/T	BAJA LEGEND MTZ™	BAJA LEGEND EXP™
PREMIUM RADIAL	Radial construction, engineered to provide a premium on-road experience.				X*				X†		
NEXT-GEN HIGH TENSILE	Radial construction which replaces the body plies used in "Premium Radial" with high tensile strength plies.										X‡
POWERPLY™	Unique radial construction utilizing two radial plies and one bias-ply.									X	
POWERPLY™ XD	Competition proven construction, adding 50% heavier denier cord to the third ply.							X	X§		
POWERPLY™ PRO	Composed of two radial plies sandwiched between two heavy-duty bias plies with added sidewall rubber gauge.					X¶	X				
PREMIUM BIAS	Bias-ply construction, designed with four nylon body plies and two belts.			X	X*						
PRO-TECH	Bias-ply construction, the sidewall and bead areas have been reinforced.		X								

*SELECT SIZES

†SUV SIZES ONLY

‡LOAD RANGES D, E, & F

§LT SIZES ONLY

¶37" SIZE USES POWERPLY™ XD



BAJA BOSS® A/T

PREMIUM HYBRID ALL-TERRAIN - R/T



PREMIUM
ON-ROAD



OFF-ROAD



SNOW



TIRE FEATURES



50K MILE (LT SIZES) & 60K MILE (SUV SIZES)

LIMITED TREADWEAR WARRANTY*

instills confidence that the Baja Boss® A/T is built to last



**THREE-PEAK MOUNTAIN
SNOWFLAKE DESIGNATION**

on all sizes 12.50 (315) and narrower



**T1 COMPOUND (LT SIZES) &
S1 COMPOUND (SUV SIZES)**

provides excellent wet handling, wet braking,
lasting tread life, and cold/wet weather traction



POWERPLY™ XD

adds an extra thick denier cord to the angled third
ply for better puncture resistance, quicker steering
response, and greater stability (LT sizes only)



EXTREME SIDEBITERS®

are 150% deeper than the Baja Legend EXP™ for a bold
look and extreme off-road traction/protection (LT sizes only)



ASYMMETRIC TREAD PATTERN

is optimized for reduced noise, off-road traction,
and on-road handling

WHY CHOOSE THE BAJA BOSS® A/T?

The Baja Boss® A/T is a premium hybrid all-terrain tire engineered for drivers who demand aggressive looks and all-weather capability without sacrificing on-road comfort. Its asymmetric tread pattern reduces noise while enhancing traction. A silica-reinforced compound improves wet braking and tread life, and PowerPly™ XD construction adds sidewall strength and steering response. With 50K-60K mileage warranties and 3PMS certification on select sizes, it's built to perform—and built to stand out.

BAJA LEGEND EXP™

HYBRID ALL-TERRAIN - R/T



PREMIUM
ON-ROAD



TRAIL



TIRE FEATURES



LIMITED TREADWEAR WARRANTY

instills confidence that the Baja Legend EXP™
is built to last



LEGENDARY "BAJA INSPIRED" TREAD STYLING

with large surface area tread elements, wide
voids for an aggressive appearance, and great
on/off-road performance



T4 SILICA-REINFORCED COMPOUND

provides excellent wet handling/braking performance,
cut and chip resistance, and lasting treadlife



**NEXT-GEN LIGHTWEIGHT
HIGH TENSILE BODY PLIES**

provides a smooth ride and durability



OPTIMIZED TREAD DESIGN AND GEOMETRY

help to reduce noise

WHY CHOOSE THE BAJA LEGEND EXP™?

The Baja Legend EXP™ is a rugged all-terrain tire built for trail leaders and daily drivers alike. Its bold tread styling and Sidebiters® deliver off-road traction and protection, while a silica-reinforced compound enhances wet handling and tread life. Lightweight high-tensile body plies provide a smooth ride and durability. Backed by a limited treadwear warranty, the EXP™ blends legendary Mickey Thompson design with modern performance.

BAJA BOSS® M/T

PREMIUM EXTREME MUD-TERRAIN



ON-ROAD



EXTREME
OFF-ROAD



COMPETITION



TIRE FEATURES



ASYMMETRIC TREAD PATTERN

is optimized for reduced noise, off-road traction, and on-road handling



EXTRA LARGE FOUR-PITCH SIDEBITERS®

for enhanced off-road traction



POWERPLY™ XD

adds an extra thick denier cord to the angled third ply for better puncture resistance, quicker steering response, and greater stability



STONE EJECTOR RIBS

prevent gravel from being wedged into tread grooves



T4 SILICA-REINFORCED COMPOUND

provides excellent wet handling/braking performance, cut and chip resistance, and lasting treadlife

BAJA LEGEND MTZ™

MUD-TERRAIN



ON-ROAD



EXTREME OFF-ROAD



TIRE FEATURES



POWERPLY™ 3-PLY SIDE WALL CONSTRUCTION

provides increased puncture resistance and more responsive handling



VARIABLE LENGTH AND DEPTH FOUR-PITCH SIDEBITERS®

provides off-road traction and grip



T4 SILICA-REINFORCED COMPOUND

designed to provide excellent wet handling/braking performance, cut and chip resistance, and lasting treadlife



BOLD & PROVEN MTZ TREAD STYLING

for an aggressive appearance and great on/off-road performance



OPTIMIZED TREAD DESIGN AND GEOMETRY

help to reduce noise

WHY CHOOSE THE BAJA BOSS® M/T?

The Baja Boss® M/T is our most advanced mud-terrain tire, designed for serious off-roaders who won't compromise. Its asymmetric tread pattern delivers off-road grip with on-road refinement. Extreme Sidebiters® on the sidewall provide added traction and protection, while PowerPly™ XD construction enhances durability and handling. A silica-reinforced compound improves wet performance and treadwear. This is competition-proven technology for those who lead the pack.

WHY CHOOSE THE BAJA LEGEND MTZ™?

The Baja Legend MTZ™ is a versatile mud-terrain tire for those who want authentic off-road performance with everyday drivability. Featuring bold tread styling and variable-depth Sidebiters®, it delivers traction in mud, rocks, and loose terrain. PowerPly™ 3-ply sidewall construction improves steering response and puncture resistance, while a silica-reinforced compound enhances wet grip and treadwear. It's built for those who want to go further—and stand out while doing it.

EXTREME TERRAIN TIRES

FROM EAST TO WEST AND EVERYWHERE IN BETWEEN, MICKEY THOMPSON'S EXTREME TIRE LINEUP DELIVERS PLENTY OF HARDCORE PERFORMANCE FEATURES TO MEET THE DEMANDS OF ENTHUSIASTS AND COMPETITORS.



ALL-NEW

BAJA BELTED™ II

PREMIUM EXTREME TERRAIN



EXTREME
OFF-ROAD



Born from the deserts and reimagined for today, the Mickey Thompson **BAJA BELTED™ II** is here. A modern evolution of an off-road legend, the BAJA BELTED™ II captures the aggressive style of the 1980s lifted 4x4 era, engineered for today's demands. Available in wide fitments for 15" and 16" wheels, innovative 17" sizes to clear modern brake systems, and unrivaled sizing for 26" and 30" wheels, the BAJA BELTED™ II brings iconic attitude to both vintage rigs and modern show builds. With its unmistakable styling and extreme sizing, it delivers a look that ensures your truck or SUV stands out from the crowd.

TIRE FEATURES



1. STEEL-BELTED RADIAL CONSTRUCTION*

engineered to minimize flat-spotting and enhance ride quality
*SELECT SIZES



2. PRECISION-TUNED TREAD PATTERN

designed for a smooth ride, longer wear, and reduced road noise



3. DEEP, VARIABLE-DEPTH SIDEBITER®

elements for superior off-road traction and sidewall protection



4. CLASSIC WHITE-OUTLINED LETTERS

on one sidewall of 15", 16", and 17" sizes for authentic vintage style



5. WIDE FOOTPRINT

designed to maximize flotation and performance over loose terrain



6. NON-DIRECTIONAL TREAD PATTERN

allows for easy cross-rotation to help extend tire life



BAJA PRO® X

PREMIUM COMPETITION EXTREME TERRAIN

 EXTREME OFF-ROAD  COMPETITION



TIRE FEATURES

-  **STICKY X1 COMPOUND**
provides ultimate grip on hard surfaces
-  **PRO-TECH CONSTRUCTION™**
with nylon bias plies to enhance off-road durability and flexibility to conform to uneven surfaces
-  **DUAL DECOUPLING GROOVES™**
for flexibility on irregular surfaces
-  **TREAD BITER™ CLEATS**
for added traction in soft terrain
-  **MASSIVE SIDEBITERS® AND ANGLED SHOULDER SCALLOPS**
engineered for ultimate traction and grip
-  **SYMMETRIC DIRECTIONAL TREAD PATTERN**
designed to provide excellent traction and cleaning power

The **BAJA PRO® X** and **BAJA PRO® X (SXS)** are the ultimate tire for rock bouncing, rock crawling, mud bogging or just showing off! With enhanced off-road durability, the BAJA PRO X and BAJA PRO X (SXS) help you tackle terrain with confidence.

BAJA PRO® XS

PREMIUM EXTREME TERRAIN

 EXTREME OFF-ROAD



TIRE FEATURES

-  **FOUR-PLY NYLON SIDEWALL CONSTRUCTION**
offers enhanced stability and durability
-  **DUAL DECOUPLING GROOVES™**
for flexibility on irregular surfaces
-  **MUD SCOOPS**
for added cleaning power
-  **MASSIVE SIDEBITERS® AND ANGLED SHOULDER SCALLOPS**
engineered for ultimate traction and grip
-  **SYMMETRIC DIRECTIONAL TREAD PATTERN**
designed to provide excellent traction and cleaning power
-  **D.O.T. CERTIFIED**
for light or occasional highway use

The **BAJA PRO® XS** is a D.O.T. approved tire designed for on and off-road rigs. With a tough 4-ply nylon sidewall construction, this tire can handle any terrain.

BAJA BOSS® X

COMPETITION PROVEN EXTREME TERRAIN



EXTREME OFF-ROAD



COMPETITION



TIRE FEATURES



STICKY X3 COMPOUND

provides ultimate grip on hard surfaces



POWERPLY™ PRO

innovative 4-ply sidewall construction for increased puncture resistance



EXTRA LARGE FOUR-PITCH SIDEBITERS®

for enhanced off-road traction



STONE EJECTOR RIBS

prevent gravel from being wedged into tread grooves

BAJA BOSS® XS

COMPETITION PROVEN EXTREME TERRAIN



EXTREME OFF-ROAD



COMPETITION



TIRE FEATURES



POWERPLY™ PRO

innovative 4-ply sidewall construction for increased puncture resistance



EXTRA LARGE FOUR-PITCH SIDEBITERS®

for enhanced off-road traction



FUNCTIONAL ASYMMETRIC PATTERN

and a silica-reinforced compound provides off-road traction



D.O.T. CERTIFIED

for highway use

The **BAJA BOSS® X** is a no-compromise, competition-centered tire featuring our sticky competition compound. Powerply™ PRO construction offers better durability, stability, and steering response, while the extra large, four-pitch Sidebiters® maximize off-road traction. The addition of our Stone Ejector Ribs prevents debris from becoming wedged into the tread grooves, maintaining consistent traction and longevity.

The **BAJA BOSS® XS** blends the functional technology that revolutionized the mud terrain market in 2019 from the Baja Boss® M/T with the competition-proven durability of the Baja Boss® X. Extreme Sidebiters® with a silica-reinforced compound provide excellent traction and durability in off-road conditions. Paired with our innovative 4-ply PowerPly™ PRO sidewall technology, the Baja Boss® XS provides purpose-built traction for the varied and sometimes unpredictable terrain of competition-style rock crawling, endurance desert racing and short course style racing.

BAJA BOSS® A/T

WHEEL DIA.	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	EQUIVALENT SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.*		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.*	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 3/2NDOS	APPROX. WEIGHT LBS.
15"	• 249344	340007003	235/75R15	29X9.00R15	XL	BLK	109T		(6.5) 6.0-8.0	50	2,271	28.8	9.2	6.7	16.0	36
	• 247497	340001003	265/70R16	31X10.50R16	STD	BLK	112T		(8.0) 7.0-9.0	44	2,469	30.8	10.5	8.6	16.0	42
16"	• 249345	340008003	265/75R16	32X10.50R16	STD	BLK	116T		(7.5) 7.0-9.0	44	2,756	31.7	10.6	7.7	16.0	42
	247455	331004001	LT265/75R16	32X10.50R16LT	E	BLK	123Q		(7.5) 7.0-9.0	80	3,415	32.0	10.7	8.2	18.5	57
16"	247464	331013001	LT285/75R16	33X11.50R16LT	E	BLK	126Q		(8.0) 7.5-9.5	80	3,750	32.9	11.7	9.3	18.5	66
	• 249346	340009003	245/65R17	30X9.50R17	XL	BLK	111T		(7.0) 7.0-8.5	50	2,403	29.8	9.7	7.7	16.0	38
16"	247348	331001001	LT265/65R17	31X10.50R17LT	E	BLK	120Q		(8.0) 7.5-9.5	80	3,085	30.5	10.7	8.7	18.5	57
	• 247499	340016003	265/70R17	32X10.50R17	XL	BLK	116T		(8.0) 7.0-9.0	50	2,756	31.9	10.4	8.6	16.0	44
16"	247454	331003001	LT265/70R17	32X10.50R17LT	E	BLK	121Q		(8.0) 7.0-9.0	80	3,195	31.9	10.7	8.7	18.5	57
	• 247502	340020003	285/70R17	33X11.50R17	STD	BLK	116T		(8.5) 7.5-9.5	44	2,756	32.8	11.6	8.9	16.0	48
17"	272481	331285001	LT285/70R17	33X11.50R17LT	E	BLK	121Q		(8.5) 7.5-9.5	80	3,195	33.0	11.5	9.3	18.5	63
	• 247463	331012001	33X12.50R17LT	-	D	BLK	114Q		(10.0) 8.5-11.0	50	2,600	32.8	12.0	10.3	18.5	68
17"	• 247462	331011001	LT305/65R17	33X12.50R17LT	E	BLK	121Q		(9.0) 8.5-11.0	65	3,195	32.8	12.0	10.3	18.5	67
	247472	331021001	LT295/70R17	34X12.00R17LT	E	BLK	121Q		(8.5) 7.5-10.0	80	3,195	33.7	12.1	10.2	18.5	72
17"	247480	331030001	LT255/85R17	35X10.00R17LT	E	BLK	121Q		(7.0) 6.5-8.0	80	3,195	34.6	10.1	8.6	18.5	64
	• 272568	331309001	35X12.50R17LT	-	D	BLK	119Q		(10.0) 8.0-11.0	50	3,000	34.5	12.8	10.3	18.5	69
17"	• 272570	331311001	LT315/70R17	35X12.50R17LT	E	BLK	121Q		(9.5) 8.0-11.0	65	3,195	34.5	12.8	10.3	18.5	71
	247490	331040001	37X12.50R17LT	-	D	BLK	124Q		(10.0) 8.0-11.0	50	3,525	36.7	13.0	10.3	18.5	80
18"	• 247496	340014003	265/60R18	31X10.50R18	XL	BLK	114T		(8.0) 7.5-9.5	50	2,601	30.8	10.6	9.0	16.0	44
	247453	331002001	LT265/60R18	31X10.50R18LT	E	BLK	119Q		(8.0) 7.5-9.5	80	3,000	30.8	10.7	8.6	18.5	57
18"	• 247498	340015003	265/65R18	32X10.50R18	XL	BLK	116T		(8.0) 7.5-9.5	50	2,756	31.5	10.7	8.5	16.0	45
	• 249347	340010003	275/65R18	32X11.00R18	STD	BLK	116T		(8.0) 7.5-9.5	44	2,756	32.4	10.9	8.7	16.0	46
18"	247470	331019001	LT275/70R18	33X11.00R18LT	E	BLK	125Q		(8.0) 7.0-9.0	80	3,640	33.4	10.8	9.6	18.5	66
	247467	331016001	LT285/65R18	33X11.50R18LT	E	BLK	125Q		(8.5) 8.0-10.0	80	3,640	33.2	10.9	10.0	18.5	64
18"	• 247459	331008001	33X12.50R18LT	-	E	BLK	118Q		(10.0) 8.5-11.0	65	2,910	32.6	11.9	10.3	18.5	67
	• 247458	331007001	LT305/60R18	33X12.50R18LT	F	BLK	126Q		(9.0) 8.5-11.0	80	3,750	32.6	11.9	10.3	18.5	68
18"	247479	331029001	LT295/70R18	34X12.00R18LT	E	BLK	129Q		(8.5) 7.5-10.0	80	4,080	34.5	11.7	10.2	18.5	73
	• 247483	331033001	35X12.50R18LT	-	D	BLK	118Q		(10.0) 8.5-11.0	50	2,910	34.6	12.8	10.3	18.5	73
18"	• 247489	331039001	LT305/70R18	35X12.50R18LT	E	BLK	126Q		(9.0) 8.0-10.0	65	3,750	35.3	12.2	10.3	18.5	75
20"	• 247495	340013003	265/50R20	31X10.50R20	XL	BLK	111T		(8.5) 7.5-9.5	50	2,403	30.4	10.7	9.3	16.0	43
	• 247500	340018003	275/55R20	32X11.00R20	XL	BLK	117T		(8.5) 7.5-9.5	50	2,833	32.2	11.1	9.5	16.0	48
20"	247456	331005001	LT275/55R20	32X11.00R20LT	E	BLK	120Q		(8.5) 7.5-9.5	80	3,085	32.2	10.9	10.0	18.5	63
	• 249348	340011003	305/50R20	32X12.50R20	XL	BLK	120T		(9.5) 8.5-11.0	50	3,086	32.2	12.0	10.4	16.0	51
20"	• 247503	340021003	275/60R20	33X11.00R20	STD	BLK	115T		(8.0) 7.5-9.5	44	2,679	33.4	10.8	9.2	16.0	47
	247469	331018001	LT275/60R20	33X11.00R20LT	E	BLK	123Q		(8.0) 7.5-9.5	80	3,415	33.4	10.8	9.6	18.5	64
20"	272483	331294001	LT285/55R20	33X11.50R20LT	E	BLK	122Q		(9.0) 8.0-10.0	80	3,305	32.7	11.5	9.7	18.5	62
	247468	331017001	LT295/55R20	33X12.00R20LT	E	BLK	123Q		(9.5) 8.0-10.5	80	3,415	33.2	12.0	10.3	18.5	67
20"	• 247461	331010001	33X12.50R20LT	-	E	BLK	114Q		(10.0) 8.5-11.0	65	2,600	32.8	12.2	10.3	18.5	68
	• 247473	331022001	LT305/55R20	33X12.50R20LT	F	BLK	125Q		(9.5) 8.5-11.0	80	3,640	33.7	12.2	10.3	18.5	70
20"	• 247457	331006001	33X13.50R20LT	-	F	BLK	120Q		(11.0) 9.5-12.0	80	3,085	32.5	13.5	11.4	18.5	73
	247478	331028001	LT275/65R20	34X11.00R20LT	E	BLK	126Q		(8.0) 7.5-9.5	80	3,750	34.5	10.8	9.6	18.5	65
20"	247471	331020001	LT285/60R20	34X11.50R20LT	E	BLK	125Q		(8.5) 8.0-10.0	80	3,640	33.6	11.3	9.2	18.5	67
	247474	331023001	LT295/60R20	34X12.00R20LT	E	BLK	126Q		(8.5) 8.0-10.5	80	3,750	34.3	11.6	10.2	18.5	69
20"	247482	331032001	LT285/65R20	35X11.50R20LT	E	BLK	127Q		(8.5) 8.0-10.0	80	3,860	34.6	11.5	9.7	18.5	69
	247485	331035001	35X12.50R20LT	-	F	BLK	125Q		(10.0) 8.5-11.0	80	3,640	34.7	12.4	10.3	18.5	73
20"	• 247477	331026001	35X13.50R20LT	-	F	BLK	126Q		(11.0) 9.5-12.0	80	3,750	34.5	13.3	11.4	18.5	80
	• 247484	331034001	35X15.50R20LT	-	F	BLK	127Q		(12.5) 11.0-14.0	80	3,860	34.6	15.4	12.6	18.5	83
20"	247491	331041001	37X12.50R20LT	-	E	BLK	126Q		(10.0) 8.5-11.0	65	3,750	36.7	12.6	10.3	18.5	80
	• 247492	331042001	37X13.50R20LT	-	E	BLK	127Q		(11.0) 8.5-12.0	65	3,860	36.7	13.5	11.1	18.5	87
22"	• 247501	340019003	285/45R22	32X11.50R22	XL	BLK	114T		(9.5) 9.0-10.5	50	2,601	32.3	11.3	9.9	16.0	49
	• 249349	340012003	305/45R22	33X12.50R22	XL	BLK	118T		(10.0) 9.5-11.5	50	2,910	33.0	11.9	10.4	16.0	52
22"	247466	331015001	33X12.50R22LT	-	F	BLK	114Q		(10.0) 8.5-11.0	80	2,600	33.0	12.0	10.3	18.5	67
	247481	331031001	LT285/55R22	35X11.50R22LT	E	BLK	124Q		(9.0) 8.0-10.0	80	3,525	34.6	11.5	9.7	18.5	68
22"	247487	331037001	35X12.50R22LT	-	F	BLK	121Q		(10.0) 8.5-11.0	80	3,195	34.9	12.1	10.3	18.5	75
	• 247488	331038001	LT325/50R22	35X13.00R22LT	F	BLK	127Q		(10.0) 9.0-12.0	80	3,860	35.0	12.8	11.9	18.5	80
22"	• 247486	331036001	35X15.50R22LT	-	F	BLK	123Q		(13.0) 12.5-14.5	80	3,415	34.7	15.2	12.7	18.5	83
	• 247493	331043001	37X13.50R22LT	-	F	BLK	128Q		(11.0) 8.5-12.0	80	3,970	36.8	13.3	11.1	18.5	86
24"	• 250092	331250001	35X15.50R24LT	-	F	BLK	117Q		(14.0) 13.0-15.5	80	2,835	34.7	15.6	12.7	18.5	81
	• 247494	331044001	37X13.50R24LT	-	F	BLK	124Q		(11.0) 8.5-12.0	80	3,525	36.8	13.6	11.1	18.5	86

*SERVICES DESCRIPTION AND MAX LOAD DATA LISTED IS FOR SINGLE REAR TIRE APPLICATIONS.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

• INCREASED-LOAD LT-METRIC OPTIONS FOR HEAVY DUTY APPLICATIONS.
• APPROVED FOR THE INCREASING POPULAR 12" AND/OR 14" WIDE WHEELS.
• LOWER-LOAD FLOTATION OPTIONS FOR JEEPS, 1/2-TONS & OFF-ROAD.
• SUV SIZES ARE A LIGHTER-DUTY ALTERNATIVE TO LT OFFERINGS.

BAJA LEGEND EXP™

WHEEL DIA.	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	EQUIVALENT SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.*		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.*	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
15"	247530	331055003	31X10.50R15LT	-	C	RWL	109Q		(8.5) 7.0-9.0	50	2,270	30.8	10.9	8.2	18.5	45
	247541	331066003	33X12.50R15LT	-	C	RWL	108Q		(10.0) 8.0-11.0	35	2,205	32.9	12.1	9.8	18.5	55
	247557	331082003	35X12.50R15LT	-	C	RWL	113Q		(10.0) 8.0-11.0	35	2,535	34.9	12.2	9.9	18.5	60
16"	249404	331280003	LT245/70R16	30X9.50R16LT	E	RWL	118Q		(7.0) 6.5-8.0	80	2,910	29.8	9.8	7.8	18.5	46
	249753	331228003	LT265/70R16	31X10.50R16LT	E	RWL	121Q		(8.0) 7.0-9.0	80	3,195	30.9	10.7	8.6	18.5	50
	247533	331058003	LT265/75R16	32X10.50R16LT	E	RWL	123Q		(7.5) 7.0-9.0	80	3,415	31.9	10.1	8.0	18.5	50
	247542	331067003	LT285/75R16	33X11.50R16LT	E	RWL	126Q		(8.0) 7.5-9.5	80	3,750	33.0	11.3	8.6	18.5	57
	247545	331070003	LT305/70R16	33X12.50R16LT	E	RWL	124Q		(9.0) 8.0-10.0	65	3,525	33.1	12.0	9.7	18.5	58
	247555	331080003	LT315/75R16	35X12.50R16LT	E	RWL	127Q		(8.5) 8.0-11.0	65	3,860	34.8	11.9	9.8	18.5	64
17"	247531	331056003	LT265/65R17	31X10.50R17LT	E	RWL	120Q		(8.0) 7.5-9.5	80	3,085	30.8	10.6	8.8	18.5	50
	272485	331295003	LT265/70R17	32X10.50R17LT	E	RWL	121Q		(8.0) 7.0-9.0	80	3,195	31.9	10.8	8.4	18.5	54
	272488	331296003	LT275/70R17	32X11.00R17LT	E	RWL	121Q		(8.0) 7.0-9.0	80	3,195	32.5	10.7	8.8	18.5	55
	272490	331297003	LT285/70R17	33X11.50R17LT	E	RWL	121Q		(8.5) 7.5-9.5	80	3,195	33.1	11.5	9.1	18.5	57
	247539	331064003	LT305/65R17	33X12.50R17LT	E	RWL	121Q		(9.0) 8.5-11.0	65	3,195	32.9	12.3	9.9	18.5	60
	247548	331073003	LT295/70R17	34X12.00R17LT	E	RWL	121Q		(8.5) 7.5-10.0	80	3,195	33.6	11.8	9.5	18.5	59
	• 272404	331303003	35X12.50R17LT	-	D	RWL	119Q		(10.0) 8.0-11.0	50	3,000	34.5	12.9	10.0	18.5	64
	• 272406	331304003	LT315/70R17	35X12.50R17LT	D	RWL	121Q		(9.5) 8.0-11.0	50	3,195	34.6	12.8	10.0	18.5	62
18"	272524	331305002	37X12.50R17LT	-	D	BLK	124Q		(10.0) 8.0-11.0	50	3,525	36.4	13.1	10.0	18.5	70
	272564	331310002	LT265/60R18	31X10.50R18LT	E	BLK	119Q		(8.0) 7.5-9.5	80	3,000	30.5	10.7	8.8	18.5	51
	247535	331060003	LT275/65R18	32X11.00R18LT	E	RWL	123Q		(8.0) 7.5-9.5	80	3,415	32.3	11.0	8.8	18.5	53
	247538	331063003	LT265/70R18	33X10.50R18LT	E	RWL	124Q		(8.0) 7.0-9.0	80	3,525	32.9	10.7	8.9	18.5	54
	272492	331299003	LT275/70R18	33X11.00R18LT	E	RWL	125Q		(8.0) 7.0-9.0	80	3,840	33.4	11.0	8.8	18.5	55
	247543	331068003	LT285/65R18	33X11.50R18LT	E	RWL	125Q		(8.5) 8.0-10.0	80	3,840	33.0	11.5	9.2	18.5	58
	247536	331061003	LT305/60R18	33X12.50R18LT	F	RWL	126Q		(9.0) 8.5-11.0	80	3,750	32.5	12.1	10.0	18.5	64
	247550	331075002	LT295/70R18	34X12.00R18LT	E	BLK	129Q		(8.5) 7.5-10.0	80	4,080	34.4	12.0	9.5	18.5	61
	• 247551	331076003	35X12.50R18LT	-	D	RWL	118Q		(10.0) 8.5-11.0	50	2,910	34.5	12.6	10.0	18.5	65
	• 247558	331083003	LT305/70R18	35X12.50R18LT	E	RWL	126Q		(9.0) 8.0-10.0	65	3,750	35.1	12.5	9.9	18.5	65
20"	272526	331306002	LT275/55R20	32X11.00R20LT	E	BLK	120Q		(8.5) 7.5-9.5	80	3,085	32.3	10.8	8.9	18.5	57
	247540	331065002	LT265/60R20	33X10.50R20LT	E	BLK	121Q		(8.0) 7.5-9.5	80	3,195	32.9	10.6	8.7	18.5	56
	272528	331307002	LT275/60R20	33X11.00R20LT	E	BLK	123Q		(8.0) 7.5-9.5	80	3,415	32.9	10.9	9.0	18.5	59
	272494	331300002	LT285/55R20	33X11.50R20LT	E	BLK	122Q		(9.0) 8.0-10.0	80	3,305	32.6	11.7	10.3	18.5	59
	249354	331017002	LT295/55R20	33X12.00R20LT	E	BLK	123Q		(9.5) 8.0-10.5	80	3,415	33.1	11.7	10.1	18.5	63
	• 249355	331010002	33X12.50R20LT	-	E	BLK	114Q		(10.0) 8.5-11.0	65	2,600	32.8	12.6	10.6	18.5	63
	• 247547	331072002	LT305/55R20	33X12.50R20LT	F	BLK	125Q		(9.5) 8.5-11.0	80	3,840	33.4	12.5	10.1	18.5	64
	247554	331079002	LT275/65R20	34X11.00R20LT	E	BLK	126Q		(8.0) 7.5-9.5	80	3,750	34.7	11.5	9.1	18.5	61
	247549	331074002	LT285/60R20	34X11.50R20LT	E	BLK	125Q		(8.5) 8.0-10.0	80	3,840	33.9	11.4	9.6	18.5	62
	249351	331132002	LT295/60R20	34X12.00R20LT	E	BLK	126Q		(8.5) 8.0-10.5	80	3,750	34.3	11.6	9.7	18.5	63
	249352	331144002	LT295/65R20	35X12.00R20LT	E	BLK	129Q		(8.5) 8.0-10.5	80	4,080	35.4	11.6	9.7	18.5	66
	272496	331301002	35X12.50R20LT	-	F	BLK	125Q		(10.0) 8.5-11.0	80	3,840	34.8	12.5	9.9	18.5	65
	247560	331085002	37X12.50R20LT	-	E	BLK	126Q		(10.0) 8.5-11.0	65	3,750	36.5	12.4	9.8	18.5	68
	• 272530	331308002	37X13.50R20LT	-	E	BLK	127Q		(11.0) 8.5-12.0	65	3,860	36.5	13.3	10.7	18.5	74

*SERVICES DESCRIPTION AND MAX LOAD DATA LISTED IS FOR SINGLE REAR TIRE APPLICATIONS.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

- INCREASED-LOAD LT-METRIC OPTIONS FOR HEAVY DUTY APPLICATIONS.
- APPROVED FOR THE INCREASING POPULAR 12" AND/OR 14" WIDE WHEELS.
 - LOWER-LOAD FLotation OPTIONS FOR JEEPS, 1/2-TONS & OFF-ROAD.

WHEEL DIA.	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	EQUIVALENT SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.*		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.*	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
15"	247876	331091004	33X12.50R15LT	-	C	BLK	108Q		(10.0) 8.0-11.0	35	2,205	32.7	12.2	9.8	21.0	60
	247887	331102004	35X12.50R15LT	-	C	BLK	113Q		(10.0) 8.0-11.0	35	2,535	34.6	13.1	10.1	21.0	71
16"	247879	331094004	LT285/75R16	33X11.50R16LT	E	BLK	126Q		(8.0) 7.5-9.5	80	3,750	33.0	11.2	8.8	19.0	63
	247885	331100004	LT315/75R16	35X12.50R16LT	E	BLK	127Q		(8.5) 8.0-11.0	65	3,860	34.5	12.6	9.7	20.5	73
17"	247881	331096004	LT285/70R17	33X11.50R17LT	E	BLK	121Q		(8.5) 7.5-9.5	80	3,195	33.0	11.5	9.0	19.0	63
	247880	331095004	33X12.50R17LT	-	D	BLK	114Q		(10.0) 8.5-11.0	50	2,600	33.0	12.3	10.4	21.0	67
	247874	331089004	LT305/65R17	33X12.50R17LT	E	BLK	121Q		(9.0) 8.5-11.0	65	3,195	32.7	12.3	9.9	21.0	67
	272562	331309004	35X12.50R17LT	-	D	BLK	119Q		(10.0) 8.0-11.0	50	3,000	34.8	12.5	10.0	21.0	71
	272566	331311004	LT315/70R17	35X12.50R17LT	E	BLK	121Q		(9.5) 8.0-11.0	65	3,195	34.6	12.6	10.0	21.0	70
	247896	331111004	37X12.50R17LT	-	D	BLK	124Q		(10.0) 8.0-11.0	50	3,525	36.8	13.0	10.2	22.0	79
	247903	331118004	40X13.50R17LT	-	C	BLK	121Q		(11.0) 8.5-11.5	35	3,195	39.8	13.6	11.0	22.0	92
	249341	331195004	42X13.50R17LT	-	C	BLK	126P		(11.0) 9.0-11.5	35	3,750	41.9	14.2	11.3	22.0	102
18"	247883	331098004	LT285/65R18	33X11.50R18LT	E	BLK	125Q		(8.5) 8.0-10.0	80	3,640	33.4	11.2	9.5	19.0	64
	247875	331090004	33X12.50R18LT	-	E	BLK	118Q		(10.0) 8.5-11.0	65	2,910	32.7	12.8	10.6	21.0	67
	247873	331088004	LT305/60R18	33X12.50R18LT	F	BLK	126Q		(9.0) 8.5-11.0	80	3,750	32.7	12.4	10.1	21.0	68
	247891	331106004	35X12.50R18LT	-	D	BLK	118Q		(10.0) 8.5-11.0	50	2,910	34.8	12.5	10.1	21.0	73
20"	272469	331294004	LT285/55R20	33X11.50R20LT	E	BLK	122Q		(9.0) 8.0-10.0	80	3,305	32.6	11.7	9.3	18.5	63
	247882	331097004	LT295/55R20	33X12.00R20LT	E	BLK	123Q		(9.5) 8.0-10.5	80	3,415	33.1	12.3	10.2	20.0	68
	247877	331092004	33X12.50R20LT	-	E	BLK	114Q		(10.0) 8.5-11.0	65	2,600	32.7	12.2	10.7	21.0	68
	247884	331099004	LT305/55R20	33X12.50R20LT	F	BLK	125Q		(9.5) 8.5-11.0	80	3,640	33.5	12.2	10.4	20.5	70
	247872	331087004	33X13.50R20LT	-	F	BLK	120Q		(11.0) 9.5-12.0	80	3,085	32.6	13.3	11.4	21.0	73
	247889	331104004	35X12.50R20LT	-	F	BLK	125Q		(10.0) 8.5-11.0	80	3,640	34.7	12.4	10.2	21.0	73
	247888	331103004	35X13.50R20LT	-	F	BLK	126Q		(11.0) 9.5-12.0	80	3,750	34.6	13.2	11.1	21.0	81
	247895	331110004	37X12.50R20LT	-	E	BLK	126Q		(10.0) 8.5-11.0	65	3,750	36.7	12.6	10.3	21.0	79
	247897	331112004	37X14.50R20LT	-	E	BLK	128Q		(11.5) 10.0-13.0	65	3,970	36.9	14.5	10.8	21.0	89
	247901	331116004	38X15.50R20LT	-	E	BLK	128Q		(12.5) 11.0-14.0	65	3,970	37.8	15.4	12.3	21.0	95
22"	249342	331197004	42X13.50R20LT	-	D	BLK	128Q		(11.0) 9.0-11.5	50	3,970	41.8	13.8	11.3	22.0	104
	249343	331199004	44X13.50R20LT	-	C	BLK	128Q		(11.0) 9.0-11.5	35	3,970	43.8	13.8	11.3	22.0	111
	247878	331093004	33X12.50R22LT	-	F	BLK	114Q		(10.0) 8.5-11.0	80	2,600	32.7	12.3	10.9	21.0	68
	247892	331107004	35X12.50R22LT	-	F	BLK	121Q		(10.0) 8.5-11.0	80	3,195	34.8	12.3	10.4	21.0	76
	247894	331109004	LT325/50R22	35X13.00R22LT	F	BLK	127Q		(10.0) 9.0-12.0	80	3,860	35.1	12.9	11.4	21.0	80
	247898	331113004	37X13.50R22LT	-	F	BLK	128Q		(11.0) 8.5-12.0	80	3,970	36.9	13.4	10.8	21.0	82
	247900	331115004	38X15.50R22LT	-	E	BLK	128Q		(12.5) 11.0-14.0	65	3,970	37.8	15.5	12.3	21.0	94
24"	247899	331114004	37X14.50R24LT	-	F	BLK	125Q		(11.5) 10.0-13.0	80	3,640	37.0	14.1	10.8	21.0	88
	247902	331117004	38X15.50R24LT	-	F	BLK	128Q		(12.5) 11.0-14.0	80	3,970	38.0	14.9	12.3	21.0	95

*SERVICES DESCRIPTION AND MAX LOAD DATA LISTED IS FOR SINGLE REAR TIRE APPLICATIONS.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

- INCREASED-LOAD LT-METRIC OPTIONS FOR HEAVY DUTY APPLICATIONS.
- APPROVED FOR THE INCREASING POPULAR 12" AND/OR 14" WIDE WHEELS.
- LOWER-LOAD FLOTATION OPTIONS FOR JEEPS, 1/2-TONS & OFF-ROAD.

BAJA LEGEND MTZ™

WHEEL DIA.	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	EQUIVALENT SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.*		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.*	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
15"	247441	331119011	31X10.50R15LT	-	C	RWL	109Q		(8.5) 7.0-9.0	50	2,270	30.8	10.7	8.5	20.0	47
	249405	331186011	33X10.50R15LT	-	C	RWL	114Q		(8.5) 7.0-9.0	50	2,600	32.8	11.2	8.6	20.0	53
	247908	331124011	33X12.50R15LT	-	C	RWL	108Q		(10.0) 8.0-11.0	35	2,205	32.7	12.2	9.8	21.0	60
	247931	331137011	35X12.50R15LT	-	C	RWL	113Q		(10.0) 8.0-11.0	35	2,535	34.6	13.1	10.1	21.0	67
16"	247904	331120011	LT265/75R16	32X10.50R16LT	E	RWL	123Q		(7.5) 7.0-9.0	80	3,415	31.9	10.7	8.4	18.5	54
	247909	331125011	LT285/75R16	33X11.50R16LT	E	RWL	126Q		(8.0) 7.5-9.5	80	3,750	33.0	11.2	8.8	19.0	60
	247910	331126011	LT305/70R16	33X12.50R16LT	E	RWL	124Q		(9.0) 8.0-10.0	65	3,525	33.0	12.3	9.9	19.5	61
	247929	331135011	LT315/75R16	35X12.50R16LT	E	RWL	127Q		(8.5) 8.0-11.0	65	3,860	34.5	12.6	9.7	20.5	68
17"	247905	331121011	LT265/70R17	32X10.50R17LT	E	RWL	121Q		(8.0) 7.0-9.0	80	3,195	31.9	10.7	8.5	18.5	54
	247921	331127011	LT285/70R17	33X11.50R17LT	E	RWL	121Q		(8.5) 7.5-9.5	80	3,195	33.0	11.5	9.0	19.0	62
	247907	331123005	LT305/65R17	33X12.50R17LT	E	BLK	121Q		(9.0) 8.5-11.0	65	3,195	32.7	12.3	9.9	21.0	64
	247924	331130011	LT295/70R17	34X12.00R17LT	E	RWL	121Q		(8.5) 7.5-10.0	80	3,195	33.5	12.0	9.7	21.0	65
	247933	331141005	35X12.50R17LT	-	D	BLK	119Q		(10.0) 8.0-11.0	50	3,000	34.8	12.5	10.0	21.0	65
	272498	331278011	LT315/70R17	35X12.50R17LT	E	RWL	121Q		(9.5) 8.0-11.0	65	3,195	34.6	12.6	10.0	21.0	67
	247939	331147005	37X12.50R17LT	-	D	BLK	124Q		(10.0) 8.0-11.0	50	3,525	36.8	13.0	10.2	22.0	80
	247940	331148005	37X13.50R17LT	-	D	BLK	121Q		(11.0) 8.5-11.5	50	3,195	36.8	13.3	11.0	22.0	81
	247959	331152005	40X13.50R17LT	-	C	BLK	121Q		(11.0) 8.5-11.5	35	3,195	39.8	13.6	11.0	22.0	91
18"	272500	331302011	LT275/70R18	33X11.00R18LT	E	RWL	125P		(8.0) 7.0-9.0	80	3,640	33.3	11.3	9.1	20.0	60
	247906	331122011	LT305/60R18	33X12.50R18LT	F	RWL	126Q		(9.0) 8.5-11.0	80	3,750	32.7	12.0	10.1	21.0	66
	247928	331134011	LT295/70R18	34X12.00R18LT	E	RWL	129P		(8.5) 7.5-10.0	80	4,080	34.5	12.0	9.7	21.0	68
	247934	331142005	35X12.50R18LT	-	D	BLK	118Q		(10.0) 8.5-11.0	50	2,910	34.8	12.5	10.1	21.0	70
	247935	331143011	LT305/70R18	35X12.50R18LT	E	RWL	126Q		(9.0) 8.0-10.0	65	3,750	35.1	12.4	9.9	21.0	70
20"	247941	331149005	37X13.50R18LT	-	D	BLK	124Q		(11.0) 8.5-11.5	50	3,525	36.8	13.3	11.0	22.0	82
	247922	331128005	LT295/55R20	33X12.00R20LT	E	BLK	123Q		(9.5) 8.0-10.5	80	3,415	33.1	12.3	10.2	20.0	64
	249356	331010005	33X12.50R20LT	-	E	BLK	114Q		(10.0) 8.5-11.0	65	2,600	32.8	12.5	10.3	21.0	65
	247925	331131005	LT305/55R20	33X12.50R20LT	F	BLK	125Q		(9.5) 8.5-11.0	80	3,640	33.5	12.2	10.4	20.5	68
	247927	331133005	LT275/65R20	34X11.00R20LT	E	BLK	126Q		(8.0) 7.5-9.5	80	3,750	34.5	10.9	9.1	19.5	63
	247926	331132005	LT295/60R20	34X12.00R20LT	E	BLK	126Q		(8.5) 8.0-10.5	80	3,750	34.3	11.5	9.7	19.5	66
	247936	331144005	LT295/65R20	35X12.00R20LT	E	BLK	129Q		(8.5) 8.0-10.5	80	4,080	35.4	11.7	9.7	19.5	69
	247932	331140005	35X12.50R20LT	-	F	BLK	125Q		(10.0) 8.5-11.0	80	3,640	34.7	12.4	10.2	21.0	70
	247937	331145005	36X15.50R20LT	-	E	BLK	126Q		(12.5) 11.0-14.0	65	3,750	36.4	15.4	12.3	21.0	90
	247938	331146005	37X12.50R20LT	-	E	BLK	126Q		(10.0) 8.5-11.0	65	3,750	36.7	12.6	10.3	21.0	77
	247942	331150005	37X13.50R20LT	-	E	BLK	127Q		(11.0) 8.5-12.0	65	3,860	36.9	13.3	10.8	21.0	82
	247958	331151005	38X15.50R20LT	-	E	BLK	128Q		(12.5) 11.0-14.0	65	3,970	37.8	15.4	12.3	21.0	94
	247960	331153005	40X14.50R20LT	-	D	BLK	128Q		(11.5) 10.0-13.0	50	3,970	39.8	14.4	11.6	22.0	94

*SERVICES DESCRIPTION AND MAX LOAD DATA LISTED IS FOR SINGLE REAR TIRE APPLICATIONS.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

- INCREASED-LOAD LT-METRIC OPTIONS FOR HEAVY DUTY APPLICATIONS.
- APPROVED FOR THE INCREASING POPULAR 12" AND/OR 14" WIDE WHEELS.
- LOWER-LOAD FLOTATION OPTIONS FOR JEEPS, 1/2-TONS & OFF-ROAD.

BAJA BELTED™ II

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
15"	276341	331314050	33X15.50R15LT	D	OWL	120P		(12.5) 11.0 - 14.0	50	3,085	32.8	15.5	TBD	18.5	TBD
	276342	331315050	17/36R15LT	C	OWL	120P		(13.5) 12.0 - 15.5	35	3,085	35.8	17.0	TBD	18.5	TBD
	276343	331316050	18.5/39R15LT	C	OWL	120P		(15.0) 13.0 - 16.5	35	3,085	38.8	18.6	TBD	21.0	TBD
16"	276344	331317050	33X15.50R16LT	E	OWL	124P		(12.5) 11.0 - 14.0	65	3,525	32.8	15.5	TBD	18.5	TBD
	276345	331318050	17/36R16LT	D	OWL	123P		(13.5) 12.0 - 15.5	50	3,415	35.8	17.0	TBD	18.5	TBD
	276346	331319050	18.5/39R16LT	C	OWL	123P		(15.0) 13.0 - 16.5	35	3,415	38.8	18.6	TBD	21.0	TBD
17"	276347	331320050	33X15.50R17LT	F	OWL	127P		(12.5) 11.0 - 14.0	80	3,860	32.8	15.5	TBD	18.5	TBD
	276348	331321050	17/36R17LT	D	OWL	125P		(13.5) 12.0 - 15.5	50	3,640	35.8	17.0	TBD	18.5	TBD
	276349	331322050	18.5/39R17LT	C	OWL	125P		(15.0) 13.0 - 16.5	35	3,640	38.8	18.6	TBD	21.0	TBD
	276351	331324052	20/44-17LT	C	OWL	126P		(16.0) 13.0 - 17.0	30	3,750	43.8	20.0	TBD	21.0	TBD
20"	276350	331323051	18.5/39R20LT	D	BLK	126P		(15.0) 13.0 - 16.5	50	3,750	38.8	18.6	TBD	21.0	TBD
	276352	331325053	20/44-20LT	C	BLK	126P		(16.0) 14.0 - 18.0	30	3,750	43.8	20.0	TBD	21.0	TBD
26"	276353	331326053	18.5/39-26LT	F	BLK	126P		(16.5) 15.5 - 18.5	75	3,750	38.8	18.4	TBD	21.0	TBD
30"	276354	331327053	19/44-30LT	D	BLK	125P		(17.0) 16.0 - 19.0	45	3,640	43.8	19.0	TBD	21.0	TBD

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
SIZING AND AVAILABILITY SUBJECT TO CHANGE.

BAJA PRO® X

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES		OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
17"	250117	331274019	43X14.50-17LT	(8.5) 8.5-11.0		42.0	16.9	15.0	27.0	114

THESE TIRES ARE NOT D.O.T. CERTIFIED.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

BAJA PRO® X (SXS)

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES		OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
14"	250116	331273019	30X10.00-14	(8.0) 7.0-8.5		30.3	10.3	9.5	27.0	46
	250115	331272019	32X10.00-14	(8.0) 7.0-8.5		31.9	10.7	9.7	27.0	49
	250114	331271019	35X10.00-14	(8.0) 7.0-8.5		34.6	12.0	9.9	27.0	63
15"	250111	331268019	30X10.00-15	(8.0) 7.0-8.5		30.2	10.0	9.4	27.0	49
	250110	331267019	32X10.00-15	(8.0) 7.0-8.5		32.0	10.8	9.8	27.0	52
	250109	331266019	35X10.00-15	(8.0) 7.0-8.5		34.3	11.7	9.9	27.0	64

THESE TIRES ARE NOT D.O.T. CERTIFIED.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

BAJA PRO® XS

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES		MAX. INFL. PSI	MAX. LOAD LBS.	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
16"	250099	331256018	19.5/46-16LT	C	BLK	(14.0) 12.0-16.0		40	3,970	46.4	21.1	16.5	27.0	149
	250096	331253018	35X13.50-17LT	C	BLK	(11.0) 9.5-12.0		30	2,470	34.6	14.0	11.5	27.0	74
17"	250095	331252018	38X13.50-17LT	D	BLK	(11.0) 9.0-11.5		55	3,195	37.9	15.3	11.8	27.0	90
	250094	331251018	40X13.50-17LT	C	BLK	(11.0) 9.0-11.5		40	3,195	39.6	15.5	11.7	27.0	99
	250097	331254018	15/43-17LT	C	BLK	(11.5) 9.5-12.5		40	3,195	42.3	18.3	13.9	27.0	125
20"	250098	331255018	15/43-20LT	C	BLK	(11.5) 9.5-12.5		40	3,935	42.6	18.0	14.2	27.0	131
	250100	331257018	19.5/46-20LT	C	BLK	(14.0) 12.0-16.0		40	3,970	46.3	19.9	16.1	27.0	149
	250101	331258018	17/49-20LT	C	BLK	(13.0) 11.0-14.0		40	3,970	47.5	19.9	14.1	27.0	162
	250102	331259018	19.5/54-20LT	C	BLK	(12.0) 12.0-16.0		40	3,970	53.7	21.6	16.9	27.0	194
24"	250103	331260018	21/58-24LT	C	BLK	(16.5) 13.5-17.5		40	3,970	57.8	22.8	17.6	27.0	233

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

BAJA BOSS® X

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
17"	250091	331249021	37X12.50R17LT	C	BLK	116F		(10.0) 8.0-11.0	35	2,755	36.8	13.0	10.2	22.0	80
	250090	331238021	40X13.50R17LT	B	BLK	115F		(11.0) 8.5-11.5	25	2,680	39.8	13.6	11.0	22.0	103
	261757	331312021	42X13.50R17LT	B	BLK	119F		(11.0) 9.0-11.5	25	3,000	41.7	14.6	11.3	22.0	104
20"	261758	331313021	42X13.50R20LT	C	BLK	124F		(11.0) 9.0-11.5	35	3,525	41.7	14.4	11.3	22.0	106

THIS TIRE IS NOT D.O.T. CERTIFIED.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

• 37X12.50R17LT USES POWERPLY™ XD CONSTRUCTION.

BAJA BOSS® XS

WHEEL DIAMETER	MATERIAL NUMBER	PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	SERVICE DESC.		(MEAS. RIM WIDTH) APPD. RIM WIDTH INCHES	MAX. INFL. PSI	MAX. LOAD LBS.	OVERALL DIAMETER INCHES	SECTION WIDTH INCHES	TREAD WIDTH INCHES	TREAD DEPTH 32NDS	APPROX. WEIGHT LBS.
17"	261886	331277013	35X12.50R17LT	C	BLK	111Q		(10.0) 8.0-11.0	35	2,405	34.8	12.5	10.0	22.0	76
	261885	331276013	37X12.50R17LT	C	BLK	116Q		(10.0) 8.0-11.0	35	2,755	36.8	13.0	10.2	22.0	86
	261884	331275013	40X13.50R17LT	B	BLK	115Q		(11.0) 8.5-11.5	25	2,680	39.8	13.6	11.0	22.0	100

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

TIRE WARRANTY

ELIGIBILITY

This warranty applies to the original purchaser of a Mickey Thompson passenger or light truck tire and is not transferable. Eligible tires must be purchased new and must be used on the vehicle which they were originally installed. Additionally, they must be an equivalent or greater load index to that specified by the vehicle manufacturer. For warranty exclusions, please refer to the complete "Mickey Thompson Passenger and Light Truck Limited Warranty" at mickeythompson tires.com or contact Mickey Thompson's technical support department at 1-800-222-9092.

STANDARD COVERAGE

If your Mickey Thompson branded tire becomes unserviceable as a result of an eligible adjustable condition during the first 2/32" of tread wear, it will be replaced with an equivalent new Mickey Thompson tire, FREE OF CHARGE. When the tread is worn more than 2/32", if the product exhibits an eligible adjustable condition, it will be replaced on a pro rated basis. For the tire pro ration schedule, please refer to the complete "Mickey Thompson Passenger and Light Truck Limited Warranty" at mickeythompson tires.com or contact Mickey Thompson's technical support department at 1-800-222-9092. You must present proof of purchase and be the original owner when requesting a replacement for your tire.

A replacement charge may be required in order to obtain a replacement tire. The replacement charge will be determined by multiplying the dealer's current selling price by the percentage of original tread depth worn from the tire. You must pay for mounting, balancing, and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.

Any Mickey Thompson tire that does not deliver satisfactory service due to a balance, out of round or a ride complaint issue will be replaced without charge within the first 2/32nds of the tire's tread life. After the first 2/32nds the tire is not warrantable for the aforementioned conditions.

TREAD LIFE

When the tread becomes worn to 2/32" (1.6mm) anywhere on the tire (shown by tread wear indicators molded into the tread grooves), the tire is worn out. WARNING—for important safety information, you must read the section titled "Tire Service Life" and Important Tire Safety and Fitment Information Warnings section of this guide. Additional Tire Safety Information is also available at mickeythompson tires.com or from your local dealer.

HOW TO OBTAIN AN ADJUSTMENT

Tire adjustments must be presented to the dealer which originally sold the tire. You must be able to provide proof of purchase and be the original owner when requesting a replacement for your tire. See "Where to Go for Warranty Replacement."

NO ROAD HAZARD COVERAGE

Many dealers sell or provide their own warranty coverage for road hazards and/or repairs. Mickey Thompson does not provide this coverage. Check with your dealer to determine if Road Hazard/Repair coverage is available from them.

TREAD WEAR PROTECTION - ELIGIBILITY

This warranty applies to the original purchaser of a replacement Mickey Thompson light truck tire and is nontransferable. Eligible tires must be purchased new and used on the vehicle which they were originally installed. Proof of purchase is required for all warranty claims. Additionally, they must be the size, load index, and speed rating equivalent or greater than that specified by the vehicle manufacturer. This warranty applies to the 48 contiguous continental United States, District of Columbia and Canada. For warranty exclusions see "WHAT ISN'T COVERED" in the Mickey Thompson Standard Warranty.

The following Tread Wear Warranty is a prorated warranty (there is no free replacement period) based on mileage received, and is separate from the Standard Coverage & Extra Coverage Warranties just covered. No manufacturer or dealer can guarantee you a certain number of miles from a given tire. Driving habits, driving conditions, tire and vehicle maintenance all play a part in the tread life of a tire and all differ with each purchaser. The following replacement Mickey Thompson Truck tires only are warranted against tread wear out prior to the applicable indicated mileage:

BAJA LEGEND EXP™

+ 50,000-mile Limited Tread Wear Warranty.

BAJA BOSS® A/T

+ 50,000-mile Limited Tread Wear Warranty on LT sizes.
+ 60,000-mile Limited Tread Wear Warranty on SUV sizes.

The Tread Wear warranty is available provided the eligibility above is met and you:

1. Are the original purchaser.
2. Rotate your tires in accordance with prescribed rotation patterns at least every 6,000 miles (10,000 km) and it must be recorded.
3. Present the tire for adjustment.
4. Present the completed rotation record form when requesting an adjustment and your original purchase receipt, date of purchase, vehicle type, model, odometer reading and rotation record are properly recorded. If the tire wears to the tread wear indicators in less than the miles warranted, a prorated adjustment will be made according to actual mileage delivered. Your adjustment credit will be determined by dividing the actual mileage delivered by the miles warranted and multiplying the result times the current selling price of an equivalent Mickey Thompson tire. Adjustment credits can only be used toward the purchase of a new Mickey Thompson tire. You must pay for mounting and balancing and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.

REPLACEMENT WARRANTY

If you receive a replacement tire under the terms of this Warranty, the replacement tire will be covered by the Warranty then currently given by Mickey Thompson for the replacement tire.

WHERE TO GO FOR WARRANTY REPLACEMENT

Contact the Mickey Thompson dealer where the tire was originally purchased for initial inspection. If the dealer which originally sold the tire is no longer available, please contact Mickey Thompson's technical support department via email at tech@mickeythompson tires.com or 1-800-222-9092 for assistance in finding a Mickey Thompson dealer (Proof of purchase will be required) You may also visit our website Dealer Locator.

CONDITIONS AND EXCLUSIONS

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Nothing in this Warranty is intended to be a representation by Mickey Thompson that tire failure cannot occur.

CONSUMER RIGHTS

This warranty does not in any way extend to any consequential or incidental damages or losses. All incidental and consequential damages and losses are hereby expressly disclaimed and excluded from this warranty. There is no other warranty, or liability, expressed or implied, applicable to these products. No representative has the authority to make any representation, promise, or agreement except as stated herein. Some states do not allow exclusion of incidental or consequential damages. As a result, this limitation or exclusion may not apply to you.

This Warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

Please refer to mickeythompson tires.com for the complete "Mickey Thompson Passenger and Light Truck Limited Warranty" or contact Mickey Thompson's technical support department at 1-800-222-9092 for additional information.

Mickey Thompson Tires shall not be liable for any incidental or consequential damages for any breach of warranty, its liability and the purchaser's exclusive remedy being expressly limited to replacement of defective wheel, as herein provided. Replacement will be handled by an authorized Mickey Thompson.

Tire Dealer or Mickey Thompson Tire representative. This warranty gives you specific legal rights. You may also have other rights under applicable laws.

FOR SERVICE ASSISTANCE OR INFORMATION CALL OR WRITE TO:

Mickey Thompson Tires
4651 Prosper Drive
Stow, OH 44224
Phone: (330) 928-9092
Fax: (330) 928-0503

READY TO BUILD SOMETHING BOLD?
EXPLORE OUR FULL LINEUP, GET EXPERT
SUPPORT, AND SEE OUR TIRES IN ACTION.

MICKEYTHOMPSONTIRES.COM
TECH SUPPORT: 800-222-9092

YOUTUBE: @MICKEYTHOMPSONTIRES
INSTAGRAM & FACEBOOK:
@MICKEYTHOMPSONTIRES

FOLLOW OUR HASHTAGS
#MICKEYTHOMPSONTIRES
#TEAMMT
#PODIUMMOMENTS



ALL SPECIFICATIONS SUBJECT TO CHANGE.
NOT RESPONSIBLE FOR TYPOGRAPHICAL ERRORS.
PRINTED IN USA - 10/2025

